

# PRB350M-J4

# AC 1U Single Removable

## Features

- 350W 6 Outputs, AC Active PFC Input Design
- Meet Intel ATX 12V/SSI EPS Requirements
- Removable Power Module for easy maintenance
- Build in DC Remote ON/OFF, PG/PF TTL Signal
- Fan Signal O/P – Frequency Generator O/P
- Build in Long Life Ball Bearing Fan
- Complies with FCC Class B, CISPR Pub. 22, EN55022 Class B, and CE requirements
- UL/cUL 60950, TUV and CB EN 60950 certified
- MTBF 100KHRs @ 25 °C per MIL-HDBK-217F
- 3 years manufacturer warranty



## Electrical Specifications

### AC Input

- |                   |              |                   |                                |
|-------------------|--------------|-------------------|--------------------------------|
| ▪ Input Voltage   | 90 – 264 VAC | ▪ Efficiency      | >63% @ full load, nominal line |
| ▪ Input Current   | 6.3A max.    | ▪ Inrush Current  | 80A max @ cold start           |
| ▪ Input Frequency | 47 – 63 Hz   | ▪ Leakage Current | 0.75mA max @ 264Vac            |

### DC Output - 350W Max

Voltage	+5V	+12V	+3.3V*	-5V*	-12V*	+5VSB*
Max load	45.0A	20.0A	28.0A	0.5A	2.0A	2.0A
Min load – Rev A	1.0-2.0A	0-1.0A	0-0.5A	0.0A	0.0A	0.0A
Min load – Rev B	0.0-1.0A	0-1.0A	0-0.5A	0.0A	0.0A	0.0A
Peak load	---	24.0A	---	---	---	---
Regulation	±3%	±3%	±3%	±10%	±5%	±5%
Ripple & Noise	50mV	120mV	50mV	100mV	120mV	50mV

- |   |   |
|---|---|
| ▪ The continuous total output power is 350W max   | ▪ Transient Overshoot: 10% max w/ 20% load change |
| ▪ The combined power of +5V and +3.3V is 230W max | ▪ Rise Time: 20 msec (maximum) @ full load        |
| ▪ The peak load on +12V lasting 15 seconds max    | ▪ Power Up Time: 800 msec (maximum) @ full load   |
| ▪ The outputs marked with " * " can be optional   | ▪ Over Power Protection: 150% max                 |
| ▪ Remote ON/OFF: TTL High/PS OFF, TTL Low/PS ON   | ▪ Over Current Protection on all outputs          |
| ▪ PG delay: 100-500 msec; PF delay: > 1 msec      | ▪ Over Voltage Protection on +5V, +12V, and +3.3V |
| ▪ Hold-Up time: 20 msec (minimum) @ full load     | ▪ Short Circuit Protection on all outputs         |

## Mechanical Dimension

- W x L x H = 150 x 185 x 40.6 mm / 5.91 x 7.28 x 1.58 inch (\* Mounting brackets and top/bottom of the cage are not included in these dimensions!)